



EonStor DS - Fibre Series

High-Availability Solutions Delivering Excellent Storage Performance

Highlights

Reliability and Availability

- Local and remote replication functionality enables quick data recovery after logical errors and physical errors
- Redundant and hot-swappable hardware components eliminate single point of failure
- Multiple hardware RAID levels protect against drive failure
- CacheSafe technology protects cached data during power outage

Performance

- Leverage 2.5" drives to achieve optimal performance density
- Hybrid connectivity models offer cost-effective remote replication and SAN tiering
- EonStor DS G7 solutions deliver superior performance ideal for mission-critical apps

Optimized Utilization

- Thin provisioning optimizes capacity utilization and simplifies storage planning and monitoring

Scalability and High Density

- Scale storage capacity (up to 240 drives) as needed through expansion enclosures
- 4U/48-bay high-density solutions meet extreme capacity requirements

Downtime can have serious consequences for enterprises and SMBs. The challenge for SMBs is to pro-actively prevent downtime within a limited budget. With today's price points in mind, the EonStor DS storage solution provides comprehensive data protection to ensure the highest data availability for the storage area network (SAN) and direct attached storage (DAS). Coupled with advanced hardware design, modular architecture, easy and intuitive management and exceptional price-performance, EonStor DS provides a decisive competitive edge by making IT efficiency keep up with growing needs. In addition, EonStor DS G7 offers superior performance levels to help companies meet demand of mission-critical applications.

High-Availability SAN

Data availability is critical to any business operation. EonStor DS features high-availability hardware designs with redundant, hot-swappable hardware components, such as RAID controllers, power supplies and cooling fans to eliminate single point of failure. Hardware RAID protection ensures data accessibility during drive failure. In the event of a power outage, CacheSafe technology will automatically leverage power of the Battery Backup Unit (BBU) to safeguard cached data by writing it to the flash module for permanent retention. To protect valuable data sets against more critical threats, EonStor DS also supports local and remote replication capabilities. Data availability can be achieved with minimal downtime in case of human errors or data volume failure by employing the EonStor DS replication features. The models supporting Small Form Factor (SFF) drives can increase performance density to support I/O-intensive applications.

Flexible Scalability and High Density

The EonStor DS storage solution supports dynamic scaling. Flexible drive type and capacity support (2.5-inch or 3.5-inch, SAS or FC, and various drive sizes) satisfies current applications and enables you to accommodate future needs. EonStor DS storage solution can be expanded to more than two hundred drives to meet the proliferation of storage growth. The "scale as you grow" flexibility of the EonStor DS storage solution minimizes upfront investments and provides the best overall Total Cost of Acquisition (TCA). In addition, 4U/48-bay solutions offer high storage density to meet extreme capacity requirements while delivering excellent cost efficiency.



EonStor DS - Fibre Series

High-Availability Solutions Delivering Excellent Storage Performance

Highlights

Management

- User-friendly and intuitive SANWatch interface allows for simple storage management

Green

- Energy efficient power supplies
- Dynamic cooling
- Intelligent multi-level drive spin-down

Intuitive and Easy Management

Storage management should be simple. The EonStor DS storage solution includes a comprehensive management software suite, SANWatch, to centrally manage multiple EonStor DS subsystems over a standard TCP/IP network. EonStor DS status and event information summary can be viewed on the portal window. Necessary functions to configure, manage and monitor the EonStor DS are only a few clicks away. Besides providing all firmware features through a user-friendly GUI, SANWatch also supports script-based configuration of multiple EonStor DS subsystems simultaneously. Automatic critical event notifications can be customized to suit the most critical storage environment. SANWatch will guide users through initializing, configuring and maintaining the EonStor DS every step of the way.

High Energy Efficiency

Contributing to environmental sustainability, EonStor DS enables energy cost-savings while maintaining performance. It is equipped with power saving designs such as high-efficiency power supplies, dynamic cooling mechanism and intelligent multi-level drive spin-down technology.

Superior Performance Levels

EonStor DS G7 systems offer superior performance levels that are ideal for mission-critical applications such as HD media editing and broadcasting, cloud services, and HPC. Featuring advanced hardware platforms, EonStor DS G7 systems provide superior throughput of up to 5,500 MB/s Read and up to 3,000 MB/s Write and support up to 700K Read IOPS.

Technical Specifications

EonStor DS: 8Gb/s FC to 6Gb/s SAS Models

| | ESDS S24F-R2840 ESDS S24F-G2840 | ESDS S16F-R2842 ESDS S16F-G2842 | ESDS S16F-R2840 ESDS S16F-G2840 | ESDS S12F-R2840 ESDS S12F-G2840 |
|--|--|--|--|--|
| Hardware Configurations | | | | |
| Storage Controller | Dual redundant or single | | | |
| Host Connectivity (per controller) | 4 x 8Gb/s FC ports | 4 x 8Gb/s FC ports + 2 x 1GbE iSCSI ports | 4 x 8Gb/s FC ports | 4 x 8Gb/s FC ports |
| Cache Memory (per controller) | Default 1GB ¹ , up to 4GB | | | |
| Drive Connectivity | 6Gb/s SAS | | | |
| Max. Drives (per system) | 24 | 16 | 16 | 12 |
| Max. Drives (via JBOD) | 104 | 112 | 112 | 84 |
| Expansion Enclosure (JBOD) | ESDS S16S-J2000-R ESDS S16S-J2000-S | ESDS S16S-J2000-R ESDS S16S-J2000-S | ESDS S16S-J2000-R ESDS S16S-J2000-S | ESDS S12S-J2000-R ESDS S12S-J2000-G |
| SAS Expansion Port | 1 x 6Gb/s SAS 4x wide port per controller | | | |
| Supported Drives ² | 300GB, 450GB or 600GB - 3.5" 15,000 RPM 6Gb/s SAS drives 1TB, 2TB or 3TB - 3.5" 7,200 RPM 6Gb/s Nearline SAS drives 300GB, 450GB or 600GB - 2.5" 10,000 RPM 6Gb/s SAS drives 500GB, 1TB, 2TB or 3TB - 3.5" 7,200 RPM 6Gb/s SATA drives ³ 100GB or 200GB - 2.5" SSDs | | | |
| Power Supplies | Three redundant 405W | Two redundant 530W | Two redundant 530W | Two redundant 530W Two redundant 350W |
| Form Factor ⁴ | 4U, 19-inch rackmount | 3U, 19-inch rackmount | 3U, 19-inch rackmount | 2U, 19-inch rackmount |
| Green | 80 PLUS-certified power supplies ⁵ delivering more than 80% energy efficiency Intelligent multi-level drive spin-down | | | |
| RAID Configurations | RAID level 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60 Up to 32 logical drives and 64 partitions per logical volume Up to 1024 LUNs | | | |
| Data Services | | | | |
| Local Replication ⁶ | Snapshot | Snapshot images per source volume Snapshot images per system | Standard License: 64 / Advanced License: 256 Standard License: 1,024 / Advanced License: 4,096 | |
| | Volume Mirror/Copy | Source volumes per system Replication pairs per source volume Replication pairs per system | Standard License: 16 / Advanced License: 32 Standard License: 4 / Advanced License: 8 Standard License: 64 / Advanced License: 256 | |
| Remote Replication ⁷ | Replication source volume Replication pairs per source volume Replication pairs per system | 16 4 64 | | |
| Thin Provisioning ⁷ | "Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space. | | | |
| Availability and Reliability | Redundant, hot-swappable hardware modules Multi-pathing support (EonPath); Device mapper support CacheSafe technology: protects cached data during power outage by flushing data into flash memory | | | |
| Management | SANWatch management suite; Embedded RAIDWatch; Terminal via RS-232C; Telnet/SSH; LCD keypad panel | | | |
| Notification | Email, Fax, LAN broadcast, SNMP traps, SMS, MSN messenger | | | |
| OS Support² | Windows Server 2003, Windows Server 2008, 2008 R2 (including Hyper-V), Windows 7 Enterprise SP1, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, HP-UX, IBM AIX, VMware, Citrix XenServer | | | |
| Service and Support⁸ | | | | |
| Standard Service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | | | |
| Upgrade/Extension Options ⁹ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | | |

1. Default capacity may vary by region.

2. For the latest compatibility details, please contact our sales representatives.

3. MUX board required when using SATA drives in dual-controller systems.

4. For detailed dimensions, please check the Infortrend website.

5. On the ESDS S16F-R2842, ESDS S16F-G2842, ESDS S16F-R2840, ESDS S16F-G2840 and ESDS S12F-R2840.

6. Standard functions come default with EonStor DS systems. Advanced functions are available with optional license.

7. Available with optional license.

8. All EonStor DS systems are shipped with Standard Service. Software maintenance covers the software licenses for EonStor DS systems.

9. Options may vary by region.

| | ESDS S48F-R2842 | ESDS S48F-G2842 | |
|--|--|--|--|
| Hardware Configurations | | | |
| Storage Controller | Dual redundant | Single | |
| Host Connectivity (per controller) | 4 x 8Gb/s FC ports + 2 x 1GbE iSCSI ports | | |
| Cache Memory (per controller) | Default 1GB ¹ , up to 4GB | | |
| Drive Connectivity | 6Gb/s SAS | | |
| Max. Drives (per system) | 48 | | |
| Max. Drives (via JBOD) | 240 | | |
| Expansion Enclosure (JBOD) | ESDS S48S-J2000-R | ESDS S48S-J2000-G | |
| • Controller | Dual redundant | Single | |
| • Host Connectivity | Two (2) 6Gb/s SAS 4x wide ports per controller | | |
| • Drive Connectivity | 6Gb/s SAS | | |
| • Drive Bays | 48 | | |
| • Power Supplies | 2+1 redundant 530W power supplies | | |
| • Form Factor / Dimensions | 4U, 19-inch rackmount / 445mm (W) x 175.9mm (H) x 873.5mm (D) | | |
| SAS Expansion Port | 1 x 6Gb/s SAS 4x wide port per controller | | |
| Supported Drives ² | 1TB, 2TB, 3TB - 3.5" 7,200 RPM 6Gb/s Nearline SAS drives 2TB or 3TB - 3.5" 7,200 RPM 6Gb/s SATA drives ³ | | |
| Power Supplies | 2+1 redundant 530W power supplies | | |
| Form Factor / Dimensions | 4U, 19-inch rackmount / 445mm (W) x 175.9mm (H) x 873.5mm (D) | | |
| Green | 80 PLUS-certified power supplies delivering more than 80% energy efficiency Intelligent multi-level drive spin-down | | |
| RAID Configurations | RAID level 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60 Up to 32 logical drives and 64 partitions per logical volume Up to 1024 LUNs | | |
| Data Services | | | |
| Local Replication ⁴ | Snapshot | Snapshot images per source volume Snapshot images per system | Standard License: 64 / Advanced License: 256 Standard License: 1,024 / Advanced License: 4,096 |
| | Volume Mirror/Copy | Source volumes per system Replication pairs per source volume Replication pairs per system | Standard License: 16 / Advanced License: 32 Standard License: 4 / Advanced License: 8 Standard License: 64 / Advanced License: 256 |
| Remote Replication ⁵ | Replication source volume Replication pairs per source volume Replication pairs per system | 16 4 64 | |
| Thin Provisioning ⁵ | "Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space. | | |
| Availability and Reliability | Redundant, hot-swappable hardware modules Multi-pathing support (EonPath); Device mapper support CacheSafe technology: protects cached data during power outage by flushing data into flash memory | | |
| Management | SANWatch management suite; Embedded RAIDWatch; Terminal via RS-232C; Telnet/SSH; LCD keypad panel | | |
| Notification | Email, Fax, LAN broadcast, SNMP traps, SMS, MSN messenger | | |
| OS Support² | Windows Server 2003, Windows Server 2008, 2008 R2 (including Hyper-V), Windows 7 Enterprise SP1, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, HP-UX, IBM AIX, VMware, Citrix XenServer | | |
| Service and Support⁶ | | | |
| Standard Service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | | |
| Upgrade/Extension Options ⁷ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

1. Default capacity may vary by region.

2. For the latest compatibility details, please contact our sales representatives.

3. Only supported on the ESDS S48F-G2842.

4. Standard functions come default with EonStor DS systems. Advanced functions are available with optional license.

5. Available with optional license.

6. All EonStor DS systems are shipped with Standard Service. Software maintenance covers the software licenses for EonStor DS systems.

7. Options may vary by region.

| | ESDS B24F-R2842 ESDS B24F-G2842 | ESDS B24F-R2840 ESDS B24F-G2840 | ESDS B12F-R2840 ESDS B12F-G2840 |
|---|--|--|--|
| Hardware Configurations | | | |
| Storage Controller | Dual redundant or single | | |
| Host Connectivity (per controller) | 4 x 8Gb/s FC ports + 2 x 1GbE iSCSI ports | 4 x 8Gb/s FC ports | 4 x 8Gb/s FC ports |
| Cache Memory (per controller) | Default 1GB ¹ , up to 4GB | | |
| Drive Connectivity | 6Gb/s SAS | | |
| Max. Drives (per system) | 24 | 24 | 12 |
| Max. Drives (via JBOD) | 144 ² | 144 ² | 108 ³ |
| Expansion Enclosure (JBOD) | ESDS B24S-J2000-R ESDS S16S-J2000-R ⁴ ESDS S12S-J2000-R ⁴ ESDS B24S-J2000-S ESDS S16S-J2000-S ⁴ ESDS S12S-J2000-G ⁴ | ESDS B24S-J2000-R ESDS S16S-J2000-R ⁴ ESDS S12S-J2000-R ⁴ ESDS B24S-J2000-S ESDS S16S-J2000-S ⁴ ESDS S12S-J2000-G ⁴ | ESDS B12S-J2000-R ESDS S16S-J2000-R ⁴ ESDS S12S-J2000-R ⁴ ESDS B12S-J2000-G ESDS S16S-J2000-S ⁴ ESDS S12S-J2000-G ⁴ |
| SAS Expansion Port | 1 x 6Gb/s SAS 4x wide port per controller | | |
| Supported Drives ⁵ | 300GB, 450GB, 600GB, 900GB - 2.5" 10,000 RPM 6Gb/s SAS drives 147GB or 300GB - 2.5" 15,000 RPM 6Gb/s SAS drives 250GB, 500GB or 1TB - 2.5" 7,200 RPM 6Gb/s SATA drives ⁶ 100GB, 200GB, 300GB, 400GB - 2.5" SSDs | | |
| Power Supplies | Two redundant 530W | Two redundant 530W | Two redundant 380W Two redundant 250W |
| Form Factor ⁷ | 2U, 19-inch rackmount | 2U, 19-inch rackmount | 1U, 19-inch rackmount |
| Green | 80 PLUS-certified power supplies ⁸ delivering more than 80% energy efficiency Intelligent multi-level drive spin-down Dynamic cooling | | |
| RAID Configurations | RAID level 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60 Up to 32 logical drives and 64 partitions per logical volume Up to 1024 LUNs | | |
| Data Services | | | |
| Local Replication ⁹ | Snapshot | Snapshot images per source volume Snapshot images per system | Standard License: 64 / Advanced License: 256 Standard License: 1,024 / Advanced License: 4,096 |
| | Volume Mirror/Copy | Source volumes per system Replication pairs per source volume Replication pairs per system | Standard License: 16 / Advanced License: 32 Standard License: 4 / Advanced License: 8 Standard License: 64 / Advanced License: 256 |
| Remote Replication ¹⁰ | Replication source volume Replication pairs per source volume Replication pairs per system | 16 4 64 | |
| Thin Provisioning ¹⁰ | "Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space. | | |
| Availability and Reliability | Redundant, hot-swappable hardware modules Multi-pathing support (EonPath); Device mapper support CacheSafe technology: protects cached data during power outage by flushing data into flash memory | | |
| Management | SANWatch management suite; Embedded RAIDWatch; Terminal via RS-232C; Telnet/SSH; LCD keypad panel | | |
| Notification | Email, Fax, LAN broadcast, SNMP traps, SMS, MSN messenger | | |
| OS Support⁵ | Windows Server 2003, Windows Server 2008, 2008 R2 (including Hyper-V), Windows 7 Enterprise SP1, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, HP-UX, IBM AIX, VMware, Citrix XenServer | | |
| Service and Support¹¹ | | | |
| Standard Service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | | |
| Upgrade/Extension Options ¹² | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

1. Default capacity may vary by region.

2. Using five ESDS B24S expansion enclosures.

3. Using six ESDS S16S expansion enclosures.

4. The ESDS S16S/S12S expansion enclosures support 300GB, 450GB, 600GB 3.5" 15,000 RPM 6Gb/s SAS drives and 500GB, 1TB, 2TB 3.5" 7,200 RPM 6Gb/s Nearline SAS drives.

5. For the latest compatibility details, please contact our sales representatives.

6. MUX board required when using SATA drives in dual-controller systems.

7. For detailed dimensions, please check the Infortrend website.

8. On the ESDS B24F-R2842, ESDS B24F-G2842, ESDS B24F-R2840 and ESDS B24F-G2840.

9. Standard functions come default with EonStor DS systems. Advanced functions are available with optional license.

10. Available with optional license.

11. All EonStor DS systems are shipped with Standard Service. Software maintenance covers the software licenses for EonStor DS systems.

12. Options may vary by region.

Technical Specifications

EonStor DS: 8Gb/s FC to 3Gb/s SAS Models

| | ESDS S24F-R1840 ESDS S24F-G1840 | ESDS S16F-R1840 ESDS S16F-G1840 | ESDS S12F-R1840 ESDS S12F-G1842 |
|--|--|--|--|
| Hardware Configurations | | | |
| Storage Controller | Dual redundant or single | | |
| Host Connectivity | 4 x 8Gb/s FC ports per controller | | |
| Cache Memory (per controller) | Default 1GB ¹ , up to 4GB | | |
| Drive Connectivity | 3Gb/s SAS | | |
| Max. Drives (per system) | 24 | 16 | 12 |
| Max. Drives (via JBOD) | 104 | 112 | 84 |
| Expansion Enclosure (JBOD) | ESDS S16S-J1000-R ES S16S-J1000-R ESDS S16S-J1000-S ES S16S-J1000-S | ESDS S16S-J1000-R ES S16S-J1000-R ESDS S16S-J1000-S ES S16S-J1000-S | ESDS S12S-J1002-R ES S12S-J1002-R ESDS S12S-J1000-G ES S12S-J1000-G |
| SAS Expansion Port (per controller) | 1 x 3Gb/s SAS 4x wide port | | |
| Supported Drives ² | 450GB or 600GB - 3.5" 15,000 RPM 6Gb/s SAS drives 1TB, 2TB or 3TB - 3.5" 7,200 RPM 6Gb/s Nearline SAS drives 300GB or 450GB - 3.5" 15,000 RPM 3Gb/s SAS drives 500GB, 1TB or 2TB - 3.5" 7,200 RPM 6Gb/s SATA drives ³ | | |
| Power Supplies | Three redundant 405W | Two redundant 530W | Two redundant 530W Two redundant 350W |
| Form Factor ⁴ | 4U, 19-inch rackmount | 3U, 19-inch rackmount | 2U, 19-inch rackmount |
| Green | 80 PLUS-certified power supplies ⁵ delivering more than 80% energy efficiency Intelligent multi-level drive spin-down | | |
| RAID Configurations | RAID level 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60 Up to 32 logical drives and 64 partitions per logical volume Up to 1024 LUNs | | |
| Data Services | | | |
| Local Replication ⁶ | Snapshot | Snapshot images per source volume Snapshot images per system | Standard License: 64 / Advanced License: 256 Standard License: 1,024 / Advanced License: 4,096 |
| | Volume Mirror/Copy | Source volumes per system Replication pairs per source volume Replication pairs per system | Standard License: 16 / Advanced License: 32 Standard License: 4 / Advanced License: 8 Standard License: 64 / Advanced License: 256 |
| Remote Replication ⁷ | Replication source volume Replication pairs per source volume Replication pairs per system | 16 4 64 | |
| Thin Provisioning ⁷ | "Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space. | | |
| Availability and Reliability | Redundant, hot-swappable hardware modules Multi-pathing support (EonPath); Device mapper support CacheSafe technology: protects cached data during power outage by flushing data into flash memory | | |
| Management | SANWatch management suite; Embedded RAIDWatch; Terminal via RS-232C; Telnet/SSH; LCD keypad panel | | |
| Notification | Email, Fax, LAN broadcast, SNMP traps, SMS, MSN messenger | | |
| OS Support² | Windows Server 2003, Windows Server 2008, 2008 R2 (including Hyper-V), Windows 7 Enterprise SP1, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, HP-UX, IBM AIX, VMware, Citrix XenServer | | |
| Service and Support⁸ | | | |
| Standard Service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | | |
| Upgrade/Extension Options ⁹ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

1. Default capacity may vary by region.

2. For the latest compatibility details, please contact our sales representatives.

3. MUX board required when using SATA drives in dual-controller systems.

4. For detailed dimensions, please check the Infortrend website.

5. On the ESDS S16F-R1840, ESDS S16F-G1840 and ESDS S12F-R1840.

6. Standard functions come default with EonStor DS systems. Advanced functions are available with optional license.

7. Available with optional license.

8. All EonStor DS systems are shipped with Standard Service. Software maintenance covers the software licenses for EonStor DS systems.

9. Options may vary by region.

Technical Specifications

EonStor DS: 4Gb/s FC to 3Gb/s SAS Models

| | ESDS S24F-R1440 ESDS S24F-G1440 | ESDS S16F-R1440 ESDS S16F-G1440 | ESDS S12F-R1440 ESDS S12F-G1440 |
|--|--|--|--|
| Hardware Configurations | | | |
| Storage Controller | | Dual redundant or single | |
| Host Connectivity | | 2 x 4Gb/s FC ports per controller | |
| Cache Memory (per controller) | | Default 1GB ¹ , up to 4GB | |
| Drive Connectivity | | 3Gb/s SAS | |
| Max. Drives (per system) | 24 | 16 | 12 |
| Max. Drives (via JBOD) | 104 | 112 | 84 |
| Expansion Enclosure (JBOD) | ESDS S16S-J1000-R ES S16S-J1000-R | ESDS S16S-J1000-R ES S16S-J1000-R | ESDS S12S-J1002-R ES S12S-J1002-R |
| | ESDS S16S-J1000-S ES S16S-J1000-S | ESDS S16S-J1000-S ES S16S-J1000-S | ESDS S12S-J1000-G ES S12S-J1000-G |
| SAS Expansion Port (per controller) | | 1 x 3Gb/s SAS 4x wide port | |
| Supported Drives ² | 450GB or 600GB - 3.5" 15,000 RPM 6Gb/s SAS drives 1TB, 2TB or 3TB - 3.5" 7,200 RPM 6Gb/s Nearline SAS drives 300GB or 450GB - 3.5" 15,000 RPM 3Gb/s SAS drives 500GB, 1TB or 2TB - 3.5" 7,200 RPM 6Gb/s SATA drives ³ | | |
| Power Supplies | Three redundant 405W | Two redundant 530W | Two redundant 530W Two redundant 350W |
| Form Factor ⁴ | 4U, 19-inch rackmount | 3U, 19-inch rackmount | 2U, 19-inch rackmount |
| Green | 80 PLUS-certified power supplies ⁵ delivering more than 80% energy efficiency Intelligent multi-level drive spin-down | | |
| RAID Configurations | RAID level 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60 Up to 32 logical drives and 64 partitions per logical volume Up to 1024 LUNs | | |
| Data Services | | | |
| Local Replication ⁶ | Snapshot | Snapshot images per source volume Snapshot images per system | Standard License: 64 / Advanced License: 256 Standard License: 1,024 / Advanced License: 4,096 |
| | Volume Mirror/Copy | Source volumes per system Replication pairs per source volume Replication pairs per system | Standard License: 16 / Advanced License: 32 Standard License: 4 / Advanced License: 8 Standard License: 64 / Advanced License: 256 |
| Remote Replication ⁷ | Replication source volume Replication pairs per source volume Replication pairs per system | 16 4 64 | |
| Thin Provisioning ⁷ | "Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space. | | |
| Availability and Reliability | Redundant, hot-swappable hardware modules Multi-pathing support (EonPath); Device mapper support CacheSafe technology: protects cached data during power outage by flushing data into flash memory | | |
| Management | SANWatch management suite; Embedded RAIDWatch; Terminal via RS-232C; Telnet/SSH; LCD keypad panel | | |
| Notification | Email, Fax, LAN broadcast, SNMP traps, SMS, MSN messenger | | |
| OS Support² | Windows Server 2003, Windows Server 2008, 2008 R2 (including Hyper-V), Windows 7 Enterprise SP1, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, HP-UX, IBM AIX, VMware, Citrix XenServer | | |
| Service and Support⁸ | | | |
| Standard Service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | | |
| Upgrade/Extension Options ⁹ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

1. Default capacity may vary by region.

2. For the latest compatibility details, please contact our sales representatives.

3. MUX board required when using SATA drives in dual-controller systems.

4. For detailed dimensions, please check the Infortrend website.

5. On the ESDS S16F-R1440, ESDS S16F-G1440 and ESDS S12F-R1440.

6. Standard functions come default with EonStor DS systems. Advanced functions are available with optional license.

7. Available with optional license.

8. All EonStor DS systems are shipped with Standard Service. Software maintenance covers the software licenses for EonStor DS systems.

9. Options may vary by region.

| | ESDS FF-R4031 ESDS FF-S4031 | ESDS F16F-R4031-6 ESDS F16F-S4031-6 | ESDS F16F-R4840 ESDS F16F-S4840 |
|--|--|--|--|
| Hardware Configurations | | | |
| Storage Controller ¹ | | Dual redundant or single | |
| No. of Host Channels | 4 or 2 ² (4Gb/s) | 4 or 2 ² (4Gb/s) | 2 per controller (8Gb/s) |
| Cache Memory (per controller) | Default 1GB, up to 2GB | Default 1GB, up to 2GB | Default 1GB ³ , up to 4GB |
| No. of Drives (4Gb/s FC) | - | 16 | 16 |
| Max. No. of Drives (via SBOD) | 224 | 224 | 112 |
| Expansion Enclosure (SBOD) | ES F16F-J4000-R ES A16F-J2430-G | ES F16F-J4000-R ES A16F-J2430-G | ES F16F-J4000-R ES A16F-J2430-G |
| No. of Drive Expansion Channels (4Gb/s FC) | 4 or 2 | 4 or 2 | 4 |
| Power Supplies | Two redundant 250W | Two redundant 530W | Two redundant 530W |
| Form Factor ⁴ | 1U, 19-inch rackmount | 3U, 19-inch rackmount | 3U, 19-inch rackmount |
| Green | 80 PLUS-certified power supplies ⁵ delivering more than 80% energy efficiency Intelligent multi-level drive spin-down | | |
| RAID Configurations | RAID level 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60 Up to 32 logical drives and 64 partitions per logical volume Up to 1024 LUNs | | |
| Data Services | | | |
| Local Replication ⁶ | Snapshot | Snapshot images per source volume Snapshot images per system | Standard License: 64 / Advanced License: 256 Standard License: 1,024 / Advanced License: 4,096 |
| | Volume Mirror/Copy | Source volumes per system Replication pairs per source volume Replication pairs per system | Standard License: 16 / Advanced License: 32 Standard License: 4 / Advanced License: 8 Standard License: 64 / Advanced License: 256 |
| Remote Replication ⁷ | Replication source volume Replication pairs per source volume Replication pairs per system | 16 4 64 | |
| Thin Provisioning ⁷ | "Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space. | | |
| Availability and Reliability | Redundant, hot-swappable hardware modules Multi-pathing support (EonPath); Device mapper support CacheSafe technology ⁸ : protects cached data during power outage by flushing data into flash memory | | |
| Management | SANWatch management suite; Embedded RAIDWatch; Terminal via RS-232C; Telnet/SSH; LCD keypad panel | | |
| Notification | Email, Fax, LAN broadcast, SNMP traps, SMS, MSN messenger | | |
| OS Support⁹ | Windows Server 2003, Windows Server 2008, 2008 R2 (including Hyper-V), Windows 7 Enterprise SP1, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, HP-UX, IBM AIX, VMware, Citrix XenServer | | |
| Service and Support¹⁰ | | | |
| Standard Service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | | |
| Upgrade/Extension Options ¹¹ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

1. Single-controller models can be upgraded to dual-controller models.

2. If the default hub function is disabled on dual-controller models, the no. of host channels can be doubled, as follows: ESDS FF-R4031: 8 or 4 / ESDS F16F-R4031-6: 8 or 4.

3. Default capacity may vary by region.

4. For detailed dimensions, please check the Infortrend website.

5. On the ESDS F16F-R4840 and ESDS F16F-S4840.

6. Standard functions come default with EonStor DS systems. Advanced functions are available with optional license.

7. Available with optional license on the ESDS F16F-R4840 and ESDS F16F-S4840.

8. CacheSafe technology only available on the ESDS F16F-R4840 and ESDS F16F-S4840.

9. For the latest compatibility details, please contact our sales representatives.

10. All EonStor DS systems are shipped with Standard Service. Software maintenance covers the software licenses for EonStor DS systems.

11. Options may vary by region.

| | ESDS S24F-R2850 ESDS S24F-G2850 | ESDS S16F-R2850 ESDS S16F-G2850 | ESDS S12F-R2850 ESDS S12F-G2850 |
|--|--|--|--|
| Hardware Configurations | | | |
| Storage Controller | Dual redundant or single | | |
| Host Connectivity (per controller) | 4 x 8Gb/s FC ports | | |
| Cache Memory (per controller) | 4GB or 8GB | | |
| Drive Connectivity | 6Gb/s SAS | | |
| Max. Drives (per system) | 24 | 16 | 12 |
| Max. Drives (via JBOD) | 232 | 240 | 228 |
| Expansion Enclosure (JBOD) | ESDS S16S-J2000-R ESDS S48S-J2000-R ESDS S16S-J2000-S ESDS S48S-J2000-G | ESDS S16S-J2000-R ESDS S48S-J2000-R ESDS S16S-J2000-S ESDS S48S-J2000-G | ESDS S12S-J2000-R ESDS S48S-J2000-R ESDS S12S-J2000-G ESDS S48S-J2000-G |
| SAS Expansion Port | 1 x 6Gb/s SAS 4x wide port per controller | | |
| Supported Drives ¹ | 100GB ,200GB or 300GB - 2.5" 3Gb/s SATA SSDs 300GB, 450GB or 600GB - 3.5" 15,000 RPM 6Gb/s SAS drives 1TB, 2TB or 3TB - 3.5" 7,200 RPM 6Gb/s Nearline SAS drives 2 TB or 3TB - 3.5" 7,200 rpm 6Gb/s SATA drives ² | | |
| Power Supplies | Three redundant 405W | Two redundant 530W | Two redundant 530W |
| Form Factor ³ | 4U, 19-inch rackmount | 3U, 19-inch rackmount | 2U, 19-inch rackmount |
| Green | 80 PLUS-certified power supplies ⁴ delivering more than 80% energy efficiency Intelligent multi-level drive spin-down | | |
| RAID Configurations | RAID level 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60 Up to 32 logical drives and 64 partitions per logical volume Up to 1024 LUNs | | |
| Data Services | | | |
| Local Replication ⁵ | Snapshot | Snapshot images per source volume Snapshot images per system | Standard License: 64 / Advanced License: 256 Standard License: 128 / Advanced License: 4,096 |
| | Volume Mirror/Copy | Source volumes per system Replication pairs per source volume Replication pairs per system | Standard License: 16 / Advanced License: 32 Standard License: 4 / Advanced License: 8 Standard License: 64 / Advanced License: 256 |
| Availability and Reliability | Redundant, hot-swappable hardware modules Multi-pathing support (EonPath); Device mapper support CacheSafe technology: protects cached data during power outage by flushing data into flash memory | | |
| Management | SANWatch management suite; Embedded RAIDWatch; Terminal via RS-232C; Telnet/SSH; LCD keypad panel | | |
| Notification | Email, Fax, LAN broadcast, SNMP traps, SMS, MSN messenger | | |
| OS Support¹ | Windows Server 2003, Windows Server 2008, 2008 R2 (including Hyper-V), Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, HP-UX, IBM AIX, VMware, Citrix XenServer | | |
| Service and Support⁶ | | | |
| Standard Service | 3-year limited hardware/software warranty and 8x5 phone, web and email support | | |
| Upgrade/Extension Options ⁷ | Replacement part dispatch on the next business day (up to 5 years) Advanced Service: 24x7 phone, web and email support + onsite diagnostics on the next business day (up to 5 years) Premium Service: 24x7 phone, web and email support + onsite diagnostics in 4 hours (up to 5 years) Extended Standard Service up to 5 years | | |

1. For the latest compatibility details, please contact our sales representatives.
2. On ESDS S12F-G2850, ESDS S16F-G2850 and ESDS S24F-G2850.
3. For detailed dimensions, please check the Infotrend website.
4. On the ESDS S16F-R2850, ESDS S16F-G2850, ESDS S12F-R2850, ESDS S12F-G2850.

5. Standard functions come default with EonStor DS G7 systems.
Advanced functions are available with optional license.
6. All EonStor DS systems are shipped with Standard Service.
Software maintenance covers the software licenses for EonStor DS systems.
7. Options may vary by region.



© 2012 Infotrend Technology, Inc. All rights reserved.
· Any information provided herein is without warranties of any kind of and is subject to change without prior notice.
· Infotrend, SANWatch, EonPath and ESVA are registered trademarks of Infotrend Technology, Inc.
· Infotrend logo is a trademark of Infotrend Technology, Inc.
· All other names, brands, or services are trademarks or registered trademarks of their respective owners.

Asia Pacific (Taipei, Taiwan)
Infotrend Technology, Inc.
Tel: +886-2-2226-0126
E-mail: sales.ap@infotrend.com

Americas (San Jose, USA)
Infotrend Corporation
Tel: +1-408-988-5088
E-mail: sales.us@infotrend.com

US East Coast Office
Tel: +1-603-610-6398
E-mail: sales.us@infotrend.com

Europe (Basingstoke, UK)
Infotrend Europe Ltd.
Tel: +44-1256-707-700
E-mail: sales.eu@infotrend.com

Germany (Munich)
Infotrend Deutschland GmbH
Tel: +49(0)89/20 70 42-650
E-mail: sales.de@infotrend.com

China (Beijing)
Infotrend Technology, Ltd.
Tel: +86-10-63106168
E-mail: sales.cn@infotrend.com

Japan (日本, 东京)
Infotrend Japan, Inc.
Tel: +81-3-5730-6551
E-mail: sales.jp@infotrend.com